

2.0 Megapixel POE IP Bullet Camera

Model: GT-IP610(B)2MP



Key Features

- 2.0 Megapixel SONY IMX Sensor
- Resolution 1920*1080p 25FPS HD
- 3.6mm fixed lens
- IR Distance 20-25 Meter
- IP66 weatherproof

Camera Specification:

Camera

Image Sensor	1/3" 2 Megapixel progressive scan Sony IMX CMOS
Effective Pixels	1920 (H) x 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/4~1/10000s
Min. Illumination	0.1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W); 0Lux/F1.2(IR on)
S/N Ratio	>50dB

Camera Features

Max. IR LEDs Length	20-25 Meter 3D DNR
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas

Lens

Focal Length	3.6mm
Max Aperture	F1.6
Angle of View	70°
Lens Type	Fixed lens

Video

Compression	H.264 / MJPEG
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate	1080P/720P(1 ~ 25/30fps)
Bit Rate	D1/CIF(1 ~ 25/30fps)
	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps

Network

Ethernet Protocol	RJ-45 (10/100Base-T)
	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour

ONVIF

Max. User Access	ONVIF Ver. 2.0
Smart Phone	10 users
	iPhone, iPad, Android, Windows Phone

General

Power Supply	DC12V, PoE (802.3af)
Power Consumption	<6W
Working Environment	-10°C~+60°C, 10%~90%
Ingress Protection	IP66

