

2.0 Megapixel IP Dome Camera

Model: GT-IP610(D)2.0MP



Key Features

- 2.0 Megapixel SONY IMX Sensor
- Resolution 1920*1080p 25FPS HD
- 3.6mm fixed lens
- IR Distance 20-25 Meter
- IP66 weatherproof

Camera Specification:

Camera		
Image Sensor		1/3" 2 Megapixel progressive scan Sony IMX CMOS
Effective Pixels		1920 (H) x 1080 (V)
Scanning System		Progressive
Electronic Shutter Speed		Auto/Manual, 1/4~1/10000s
Min. Illumination		0.1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W); 0Lux/F1.2(IR on)
S/N Ratio		>50dB
Camera Features		
Max. IR LEDs Length		20-25Meter 3D DNR
Day/Night		Auto(ICR)/Color/B/W
Backlight Compensation		BLC / HLC / DWDR
White Balance		Auto
Noise Reduction		2D
Privacy Masking		Up to 4 areas
Lens		
Focal Length		3.6mm
Max Aperture		F1.6
Angle of View		70°
Lens Type		Fixed lens
Video		
Compression		H.264 / MJPEG
Resolution		1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate	Main Stream	1080P/720P(1 ~ 25/30fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate		H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps
Network		
Ethernet		RJ-45 (10/100Base-T)
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
ONVIF		ONVIF Ver. 2.0
Max. User Access		10 users
Smart Phone		iPhone, iPad, Android, Windows Phone
General		
Power Supply		DC12V, PoE (802.3af)
Power Consumption		<6W
Working Environment		-10°C~+60°C, 10%~90%
Ingress Protection		IP66

