

2.4 Megapixel IP Dome Camera

Model: GT-IP610H(D)-2.4M



Key Features

- 2.4 Megapixel IP Camera
- Sony CMOS IMX323 Image
- 25FPS 1080
- IP66 weatherproof

Camera Specification:

Image Sensor	Hi3516CV200+IMX323
TV System	PAL/NTSC
Image Resolution	up to UXGA (1600*1200)
Horizontal Resolution	2.4MP
SYNC.	Internal
Video Out	1.0Vp-p Composite Signal (75ohm)
Minimum illuminator	0.001Lux (Infrared Light Open)
Gamma adjust	0.45
S/N Ratio	58dB(min)(AGC closed)
Lens	2.8 mm HD 3MP Lens
Leds	24 pcs IR Led
IR Distance	25M
DNR	Yes
AWB & AGC	AUTO
BLC	ON/OFF
Day/Night	Yes
Compression Technology	H.264 Main Profile @level 3
Encoding Type	CBR or VBR
Image intensification	Brightness, Contrast, Saturation, HU Adjustable
Subtitle Input	Support Channels name, Date & time
Video Orientation	Left & Right Mirror, Up & down Flip
Audio input	Optional
Audio Format	G.711/G.726
Alarm	Motion Detection(Sensitivity adjustable)
Alert Processing	Control Center monitoring, go to preset point, Email send MSG, Log Record, Video & PIC save on PC
Network Port	Ethernet(10M/100M Base-T),RJ45
Safety	IP Address Filtering, User rank protect, User login log
Software management	CMS, Onvif support different platform software
Video Protocol	TCP,UDP,IP,HTTP,FTP,SMTP,DHCP,DNS,A
Network Port	Support DDNS, P2P(NAT),software remote access
PoE	Optional
Power Input	DC12V±1V
Operation Temperature	Temperature -10°C~+75°C, Humidity less than 85%RH
Video Output	1.0Vp-p,75Ω

